

Orkus™

ESSENCE



- Substantial energy saving upto 80%
- Longer life with low lumen depreciation
- High light output and high efficiency
- Even light distribution and excellent color rendering
- Instant start and flicker free operations
- Both warm and cool colors are available



LAMP TYPE	Tube Config & Dia	Watt W	Equivalent GLS wattage	Color Temp °K	Lamp Cap IEC	Range Voltage V	Lumen lm CDL / WL	Power Factor	Life (avg.) hrs.
5W 2U - T3	2U-T3	5	25	6500/2700	B22/E27/E14	130-280	210/225	0.85	6000
8W 3U - T3	3U-T3	8	40	6500/2700	B22/E27/E14	130-280	376/400	0.85	6000
9W 2U - T4	2U-T4	9	40	6500/2700	B22/E27	130-280	423/450	0.85	6000
11W 2U - T4	2U-T4	11	60	6500/2700	B22/E27	130-280	570/610	0.85	6000
15W 2U - T4	2U-T4	15	75	6500/2700	B22/E27	130-280	810/850	0.85	6000
20W 3U - T4	3U-T4	20	100	6500/2700	B22/E27	130-280	1120/1200	0.85	6000
23W 3U - T4	3U-T4	23	120	6500/2700	B22/E27	130-280	1290/1380	0.85	6000
15W 4U - T3	4U-T3	15	75	6500/2700	B22/E27	130-280	810/850	0.85	6000