



Orkus™

NONRETROFIT / SLIM

- Saves upto 80% energy when compared with ordinary bulb
- Color Rendering Index (CRI) is more than 80% which reduces eye strain
- Fit into all existing holders, no need to change in electrical fittings
- Life upto 8000 hrs.
- Low Lumen decline & a long life-span
- Both warm and cool colors are available

LAMP TYPE	PIN TYPE	Watt W	Color Temp °K	Lamp Cap IEC		Lumen lm CDL / WL	Life (avg.) hrs.
OL - 9W	2 & 4	9	6500/2700	G23 2PIN	2G7 4PIN	565/600	8000
OL - 11W	2 & 4	11	6500/2700	G23 2PIN	2G7 4PIN	850/900	8000
OLD 10W	2 & 4	10	6500/2700	G 24 d1 2PIN	G 24 q1 4PIN	565/600	8000
OLD 13W	2 & 4	13	6500/2700	G 24 d1 2PIN	G 24 q1 4PIN	850/900	8000
OLD 18W	2 & 4	18	6500/2700	G 24 d2 2PIN	G 24 q2 4PIN	1130/1200	8000
OLD 26W	2 & 4	26	6500/2700	G 24 d3 2PIN	G 24 q3 4PIN	1800/1900	8000
OLL 18W	4	18	6500/2700	2G11 4PIN		1130/1200	8000
OLL 36W	4	36	6500/2700	2G11 4PIN		2800/2900	8000

